



Prod. N 121905

BEXOL DRACO LS GL 5 80W-90

Description	<p>This is a mineral lubricating oil for mechanical transmissions, formulated with high quality solvent refined base oils and special EP-additives to obtain the following properties:</p> <ul style="list-style-type: none">- an excellent resistance against oxidation- a very high activity against wear, corrosion and foam- a low pour point- very good EP-properties- excellent "Limited Slip" properties												
Application	<p>This gear oil has especially been developed for the perfect lubrication of so-called "Limited Slip" and "Auto-Locking" hypoid transmissions.</p>												
Specifications	<p>Performance level API GL-5 MIL-L-2105D ZF TE-ML 05C</p>												
Typicals	<table><tr><td>Density at 15 °C, kg/l</td><td>0,903</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>150,00</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>15,10</td></tr><tr><td>Viscosity Index</td><td>100</td></tr><tr><td>Flash Point COC, °C</td><td>210</td></tr><tr><td>Pour Point, °C</td><td>-30</td></tr></table>	Density at 15 °C, kg/l	0,903	Viscosity 40 °C, mm ² /s	150,00	Viscosity 100 °C, mm ² /s	15,10	Viscosity Index	100	Flash Point COC, °C	210	Pour Point, °C	-30
Density at 15 °C, kg/l	0,903												
Viscosity 40 °C, mm ² /s	150,00												
Viscosity 100 °C, mm ² /s	15,10												
Viscosity Index	100												
Flash Point COC, °C	210												
Pour Point, °C	-30												