

BEXOL HEAVY ULTRA LSP EXTRA LD 5W-30

Description	LB Turbosynth LSP Plus 5W30 is a product of the LB (Level Back-up) product range. These products are based on the officially approved formulas, using the same high-quality additives, but the base oils have been replaced with equivalent alternatives. This creates equivalent products in terms of quality, with a performance level corresponding to the originally approved products. However, because no field tests have been conducted, the product may be claimed only to meet the mentioned performance levels.	
Application	This fuel saving lubricant has mainly been developed for heavy diesel engines even under the toughest operation conditions and all the year round. This product is very suitable for Euro 5 and Euro 6 engines in combination with diesel fuel with a low sulphur content. This engine oil is also suitable for application in engines with or without particle filters and exhaust catalyts. This motoroil is one of the group "low SAPS" lubricants.	
Performance Level	Performance level ACEA E6, E7, E9 API CJ-4/SN Cat ECF-3 Cummins CES 20081 Detroit Diesel 93K218 Deutz DQC IV-10 LA JASO DH-2 Mack EO-O PP/EO-N PP/EO-M Plus MAN M 3677/M 3477/M 3271-1 MB 228.31/228.51 MTU Type 3.1 Renault VI RLD-3 Scania Low Ash/LDF-4 Voith Class B Volvo VDS-4/VDS-3	
Typicals	Density at 15 °C, kg/l	0,855
	Viscosity -30 °C, mPa.s	6250
	Viscosity 40 °C, mm ² /s	68,40
	Viscosity 100 °C, mm ² /s	11,50
	Viscosity Index	163
	Flash Point COC, °C	216
	Pour Point, °C	-39
	Total Base Number, mgKOH/g	9,3
	Sulphate Ash, %	0,99