Printing date 08.09.2011 Version number 2 Revision: 08.09.2011

1 Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name: BEXOL HEAVY SUPER M SHPD 20W-50

· Article number: 120910

· Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC24 Lubricants, greases, release products ·

Process category

PROC1 Use in closed process, no likelihood of exposure

PROC2 Use in closed, continuous process with occasional controlled exposure

PROC8a Transfer of substance or preparation (charging/discharging) from /to vessels/large containers at non-dedicated facilities

PROC8b Transfer of substance or preparation (charging/discharging) from /to vessels/large containers at dedicated facilities

PROC9 Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC20 Heat and pressure transfer fluids in dispersive, professional use but closed systems ·

Environmental release category

ERC4 Industrial use of processing aids in processes and products, not becoming part of articles

ERC7 Industrial use of substances in closed systems

ERC9a Wide dispersive indoor use of substances in closed systems

ERC9b Wide dispersive outdoor use of substances in closed systems

- · Application of the substance / the preparation Lubricating oil
- · Details of the supplier of the safety data sheet ·

Manufacturer/Supplier:

AS Handelsunternehmen Koenigin-Elisabeth-Str. 56 14059 Berlin, Germany 0049 30 60983171

- · Further information obtainable from: Product safety department 0049 30 60983171.
- · Emergency telephone number: 0049 30 60983171 (9 AM to 4 PM, Monday to Friday)

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified according to the CLP regulation.

- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC Not applicable.
- · Information concerning particular hazards for human and environment:

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- · Labelling according to EU guidelines:

Observe the general safety regulations when handling chemicals.

The product is not subject to identification regulations under EU Directives and the Ordinance on Hazardous Materials (German GefStoffV).

· Special labelling of certain preparations:

Safety data sheet available for professional user on request.

(Contd. on page 2)

(Contd. of page 1)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.09.2011 Version number 2 Revision: 08.09.2011

Trade name: BEXOL HEAVY SUPER M SHPD 20W-50

· Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Dangerous components:

CAS: 84605-29-8 EINECS: 283-392-8 Reg.nr.: 01-2119493626-26 Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts

Xi R38-41; N R51/53

Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin Irrit. 2, H315

· Additional information:

The highly refined mineral oil contains <3% (w/w) DMSO extract, according to IP346. For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water. ·

After swallowing: Do not induce vomiting; call for medical help immediately.

Information for doctor:

· Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, dry chemical, or foam. Water can be used to cool and protect exposed material.

For safety reasons unsuitable extinguishing agents: Water with full jet

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Wear protective clothing.

Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Remove from the water surface (e.g. skim or suck off).

(Contd. on page 3)

_GB

(Contd. of page 2)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.09.2011 Version number 2 Revision: 08.09.2011

Trade name: BEXOL HEAVY SUPER M SHPD 20W-50

· Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Avoid the formation of oil haze.

- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities · Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle. Information about storage in one common storage facility: Not required. Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

Contains mineral oil. Under conditions which may generate mists, observe the OSHA PEL of 5 mg per cubic meter, ACGIH STEL of 10 mg per cubic meter.

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.

Respiratory protection: Not required.

- · Protection of hands: Oil resistant gloves
- · Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

PVC gloves

Neoprene gloves

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling ·

Body protection: Protective work clothing

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

· Appearance:

Form: Fluid

(Contd. on page 4)

Printing date 08.09.2011 Version number 2 Revision: 08.09.2011

Trade name: BEXOL HEAVY SUPER M SHPD 20W-50

(Contd. of page 3) Colour: Brown Odour: Characteristic · Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: Undetermined. Drip point: Pour point -21°C · Flash point: > 101°C Ignition temperature: 200°C · Self-igniting: Product is not selfigniting. · Danger of explosion: Product does not present an explosion hazard. Density at 20°C: 0.883 g/cmi · Solubility in / Miscibility with Not miscible or difficult to mix. water: · Viscosity: 40°C 153 mml/s Solvent content: Organic solvents: 0.0 %

No further relevant information available.

10 Stability and reactivity

Other information

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

To avoid thermal decomposition do not overheat.

- · Possibility of hazardous reactions Reacts with strong oxidizing agents.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Product contains mineral oils of types shown to be noncarcinogenicin animal skin-painting studies. Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC). Other components are not known to be associated with carcinogenic effects.

GB

(Contd. on page 5)

Printing date 08.09.2011 Version number 2 Revision: 08.09.2011

Trade name: BEXOL HEAVY SUPER M SHPD 20W-50

(Contd. of page 4)

12 Ecological information

- · Toxicity
- · Acquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available. ·

Other information: The product is difficultly biodegradable.

- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available. ·

Mobility in soil No further relevant information available.

- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · European waste catalogue
 - 13 02 05* mineral-based non-chlorinated engine, gear and lubricating oils
- · Uncleaned packaging:
- · **Recommendation:** Disposal must be made according to official regulations.

UN-Number	
ADR, ADN, IMDG, IATA	Void
UN proper shipping name	
ADR, ADN, IMDG, IATA	Void
Transport hazard class(es)	
ADR, ADN, IMDG, IATA	
Class	Void
Packing group	
ADR, IMDG, IATA	Void
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.

(Contd. on page 6)

Printing date 08.09.2011 Version number 2 Revision: 08.09.2011

Trade name: BEXOL HEAVY SUPER M SHPD 20W-50

(Contd. of page 5)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations:
- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Department issuing MSDS:** Product safety department. ·

Contact: Product safety department

Abbreviations and acronyms:

ADR: Accord europĕen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Ruglement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

Sources

67/548/EEC - Dangerous Substances Directive

99/45/EEC - Dangerous Preparations Directive

* Data compared to the previous version altered.

_GB